

START NOW!

**SMART AND INDIVIDUAL
HEATING CONTROL**

Starter set Heating Control – WLAN

HmIP-SK13


Easily get started with your own smart home, using the intuitive Homematic IP app and radiator thermostats that are conveniently operated. Thanks to the individual heating profiles, the heating is only activated when it is needed. The heart of the smart home is formed by the flexible WLAN Access Point. It is simply connected to the wireless network via the app.



homematic ^{IP}
Smart Living, Simply Exciting.



Individual heating profiles via the free Homematic IP app



EASY WAY INTO THE SMART HOME WORLD

Flexible extension to a comprehensive smart home is possible at any time thanks to the large Homematic IP product range.

TECHNICAL SPECIFICATIONS

WLAN Access Point:

| | |
|--|---------------------------|
| Supply voltage | Power supply unit (5 VDC) |
| Supply voltage plug-in mains adapter (input) | 100 V-240 V/50 Hz |
| Ambient temperature | 5 to 35 °C |
| Dimensions (W x H x D) | 100 x 40 x 19 mm |
| Typical open area RF range | 250 m |

Radiator Thermostat:

| | |
|----------------------------|------------------------|
| Supply voltage | 2x 1.5 V LR6/mignon/AA |
| Battery life | 2 years (typ.) |
| Ambient temperature | 0 to 50 °C |
| Dimensions (W x H x D) | 57 x 68 x 102 mm |
| Typical open area RF range | 250 m |
| Threaded connection | M30 x 1.5 mm |

For further technical details and information, please refer to the data sheet of the respective device.

COMFORT TEMPERATURE AT ALL TIMES

The room temperature is controlled according to the individual needs of the user: simply via app, whether at home or on the road, directly on the device or conveniently via voice control (via Amazon Alexa or Google Assistant).

SAVES HEATING COSTS

Individual temperature profiles can easily be created via the app – with up to 3 configurable heating profiles and 13 changes per day. In this way, the heating is switched on only if needed.

OPEN-WINDOW DETECTION

Open windows are identified via the open-window detection or even more precisely in connection with the Homematic IP Window and Door Contact. The room temperature is automatically reduced to avoid any waste of energy.

SECURE AND EASY INSTALLATION

The union nut enables secure installation to standard radiator valves. Installation is quick and easy without interfering with the heating system or draining water from the radiator.

MANY ADDITIONAL FUNCTIONS

- ✓ Boost function: quick heating of rooms
- ✓ Eco mode: energy-saving operation with reduced room temperature
- ✓ Valve protection function: protects against calcification
- ✓ Operating lock: against unintended operation

LOGISTICAL DATA

| | |
|------------------------|-------------------|
| Product reference | 155703A0 |
| EAN code | 4047976557035 |
| Short description | HmIP-SK13 |
| Packing unit | 18 |
| Packing dimensions | 185 x 280 x 97 mm |
| Weight incl. packaging | 788.8 g |

PACKAGE CONTENTS

- Homematic IP WLAN Access Point (plug-in mains adapter)
- Homematic IP Radiator Thermostat – basic (2x)
- Danfoss RA adapter
- Batteries
- Mounting accessories
- User manual